

# WETSOFT

## Water Softener

Water Engineering Technologies WETSOFT range of filtration systems is the result of many years' experience in the development of water treatment plant. These softeners are developed to efficiently remove calcium and magnesium hardness minerals from the feed water and provide a cost effective solution for all hard water problems.

Our advanced technology, rugged construction and proven reliability ensure many years of reliable and carefree operation.

These systems incorporate a robust, corrosion resistant design, with an automatic multiport control valve systems and fiberglass vessel.



### Features & Benefits

- Corrosion resistant fiberglass vessel
- Top mount control valve
- Time control backwash cycles
- Minimal operator involvement
- Easy to maintain, reliable

### Applications

- Reverse Osmosis
- Apartments
- Hotels
- Hospitals
- Laundries
- Boilers



# WETSOFT Water Softener

Tanks: 10" to 63" Diameter

## WATER SOFTENING SYSTEM - SOFTENER

Model No.	Diameter, Inch	Height, Inch	Resin Bed Depth, mm	Resin Volume, Liters	Inlet Hardness	OBR at Max. flow, m3	Service Hr at Max. flow	Flow rate, m3/hr		Backwash Flow rate m3/hr	Salt, Kg 100% Conc.	Brine Tank Volume, Liter
								Min	Max			
WETSOFT-0844	08	44	800	25.000	150	6.0	12	0.30	1.20	0.30	4.5	100
WETSOFT-1054	10	54	800	41.000	150	18.13	12	0.51	1.51	0.46	7.4	100
WETSOFT-1252	12	52	800	59.00	150	26.10	12	0.73	2.18	0.66	10.6	100
WETSOFT-1354	13	54	800	69.00	150	30.63	12	0.86	2.55	0.77	12.4	100
WETSOFT-1465	14	65	1000	100.00	150	44.41	12	0.99	3.70	0.89	18.0	100
WETSOFT-1665	16	65	1000	130.00	150	58.00	12	1.30	5.5	1.17	23.4	150
WETSOFT-1865	18	65	1000	165.00	150	73.41	12	1.64	7.0	1.48	29.7	200
WETSOFT-2162	21	62	1000	224.00	150	99.92	12	2.24	11.0	2.01	40.3	300
WETSOFT-2472	24	72	1000	293.00	150	130.51	12	2.92	14.0	2.63	52.7	300
WETSOFT-3072	30	72	1000	457.00	150	203.92	12	4.57	16.99	4.11	82.3	500
WETSOFT-3672	36	72	1000	658.00	150	293.64	12	6.57	24.47	5.92	118.5	750
WETSOFT-4272	42	72	1000	895.00	150	399.68	12	8.95	33.31	8.05	161.0	1000
WETSOFT-4872	48	72	1000	1170.00	150	522.03	12	11.69	43.50	10.52	210.6	1200
WETSOFT-6367	63	67	1000	2015.00	150	899.28	12	20.13	74.94	18.12	363.0	2000



The information provided in this brochure contains merely general descriptions or characteristics of performance which in actual case of use do not always apply as describe or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of the contracts. Subject to change without prior notice.